

b&p *Manufacturing*

Product Catalog

2009

Engineered Delivery Products

www.bpmfg.com



AMERICA'S LEADING MANUFACTURER OF HIGH QUALITY DELIVERY PRODUCTS

B & P Manufacturing has been engineering material handling products since 1945 where we began as Brooks & Perkins. Since then our products and processes have seen dramatic changes in order to keep in step with the changes of the industries that our products serve.




In 1996 we completely re-engineered our product lines, replacing old designs with newer, lighter weight and more durable designs.



Over the past 5 years we have made major investments in state of the art equipment and engineering personnel all with one goal in mind, to offer our customers the best built best backed products in the industry.





By utilizing cutting edge technologies, such as our solid modeling software, we can go from concepts to full production in record time. This also allows us to respond rapidly to changes based on customer needs, and respond to new opportunities as the markets evolve.



We continue to invest in the latest equipment. This reduces our dependency on outside suppliers, and increases our production capacity while maintaining the highest level of quality in the industry.



Our inventory levels of both raw materials and completed goods are expertly maintained. Whether you need one handle or 5,000 hand trucks, we respond quickly to customer needs.



4 Terms and Conditions

CREDIT TERMS

1. **PAYMENT:** Net 30 Days
2. **FOB:** Factory or manufacturing location
3. **CREDIT APPROVAL:** Seller reserves the right at any time to revoke any credit extended to Buyer as a result of Buyer's failure to pay for merchandise when due or for any other reason deemed good and sufficient by the Seller and in such event to require payment prior to shipment.

ORDER HANDLING

1. **ACCEPTANCE & APPROVAL:** Buyer's orders submitted shall become binding and effective only upon acceptance & approval by the Seller at its office in Cadillac, Michigan
2. **BUYER'S CONFIRMATION OF TELEPHONE ORDERS:** Buyer must confirm all telephone orders in writing to the Seller's representative with whom the verbal order was placed. If the written order is not marked "confirming" and duplicate shipment results, freight, restocking and other charges are the responsibility of the Buyer.
3. **ACKNOWLEDGMENTS:** When required, Seller will mail written acknowledgments to the Buyer for all Buyer's accepted and approved orders.
4. **ADDITIONS TO PURCHASE ORDERS:** Additions to purchase orders that have already been processed by the Seller will create delays in production of the items ordered. It is to the Buyer's benefit to enter a separate purchase order for these items. Every effort will be made to see that these orders ship on a common bill of lading with the original order when requested by Buyer; however, Seller accepts no responsibility for freight charges in the event this request cannot be met.

PRICING POLICIES

1. **TAXES:** Prices do not include federal, state or local taxes.
2. **PRICE CHANGES:** B&P reserves the right to make any price changes as needed.

CONDITIONS OF SALE

1. **LOSS OR DAMAGE IN TRANSIT:** Seller inspects and makes delivery to the carrier at the shipping point in good condition. Carrier acts as Buyer's agent. Seller shall not be liable for non-arrival made under this contract which may be lost in transit; nor for losses, damages or delays in transportation. Loss or damage should be noted on the delivery receipt and claims should be made directly to the transportation company immediately.
2. **ROUTING:** Shipments will be routed "BEST WAY" transportation charge COLLECT unless otherwise requested. Every effort will be made to comply with desired routing. "Prepaid" freight cost will be invoiced directly to the Buyer.
3. **PRODUCT SPECIFICATIONS:** We reserve the right to make any changes in product specifications and designs without liability. Weights are approximate and for informational purposes only. Seller assumes no further liability, expressed or implied.
4. **CANCELLATIONS:** Orders, once acknowledged by Seller, can be cancelled only with Seller's consent and upon terms and conditions that will indemnify seller against losses.
5. **RETURNED GOODS AUTHORIZATION (RGA):**
 - a. Before returning any merchandise for any reason whatsoever, it is necessary to contact us for approval. If approval is given, an RGA number will be given by us to the dealer. This RGA number must appear on all documents involving the returned goods. Under no circumstances will returned goods be accepted at our dock without an RGA number shown on the shipping papers.
 - b. A written confirmation of each RGA will be mailed by B&P to distributor.
 - c. Freight charges on all RGA's must be prepaid.
 - d. RGA numbers will not be issued after thirty (30) days from date of shipment by B&P Manufacturing except on warranty claims. Issued RGA's will expire in thirty (30) days if returned goods have not been received by B&P Manufacturing or its designated representative. Applicable goods will not be accepted thereafter.
 - e. A minimum restocking charge of 20% will be made on all merchandise except as allowed under warranty claims.
 - f. Additional charges will be determined solely by B&P Manufacturing if the product is in a non-resalable condition.

g. Returns will not be allowed on any "Special" items determined solely obsolete products and products in non re-salable condition.

6. FIELD REPAIR AUTHORIZATION (FRA):

Before repairing any product on which a claim will be made, it is necessary to contact us for approval. Approval occurs only when FRA number is given. A written confirmation of the FRA will be mailed to you confirming the item involved, nature of repair and approved expenditure payment. Under no circumstance should you repair an item without prior FRA.

7. DELAYS IN SHIPMENT: Seller will make every effort to make shipments in accordance with the acknowledged scheduled shipping date, but Seller assumes no responsibility for any loss or inconvenience caused by non-shipment at a specified time. Cancellation requests due to delays in shipment shall be handled in accordance with Section 4 titled "Cancellations", unless Buyer and Seller mutually agree on a "No Later Than" date and order is acknowledged to that effect.

8. OSHA: Seller certifies that all terms furnished comply with Seller's interpretation of the Occupational Safety and Health Act of 1970 standards and regulations at time of shipment. Seller shall not be responsible for fines and penalties under this act or for losses sustained by improper use of any item. This is the sole certification and supercedes any, and all prior expressed or implied certifications.

9. FREIGHT COST QUOTED BY B&P MANUFACTURING:

Upon dealer request, B&P Manufacturing will obtain a freight quotation for shipment FOB, Cadillac, Michigan or point of manufacture. This service is advisory only. Responsibility for correct freight costs rests with dealer.

10. WARRANTY: The seller warrants to the original Purchaser that the items covered by this agreement shall be free from defects in material and workmanship under the normal use and service for a period of one year from the date of shipment to the seller. If within such a period any such product is proved to be so defective, such product shall be repaired or replaced at Seller's option. Seller's obligation is limited to such repair and replacement and is conditioned upon Seller's receiving written notice of any alleged defects within the warranty period and no more than (10) days after its discovery. After written approval by the Seller, the product or defective part must be returned to the seller, FOB, its factory. The term "Original Purchase" as used in this warranty shall mean the person or entity to whom such product was shipped by Seller or its distributor or Seller's agent.

This warranty shall not apply to products or parts repaired or altered by other than the Seller or subject negligence, accident, abuse, misuse or damage.

This warranty does not apply to parts subject to wear.

With respect to parts not manufactured by Seller, the warranty obligations of the Seller shall in all respects conform and be limited to the warranty actually extended to seller by the supplier.

THE FORGOING WARRANTY IS EXCLUSIVE AND EXPRESSLY IN LIEU OF ALL OTHER EXPRESS AND IMPLIED WARRANTIES WHATSOEVER. INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. SELLER SHALL NOT BE SUBJECT TO ANY OTHER OBLIGATION OR LIABILITIES WHATSOEVER WITH RESPECT TO ITS PRODUCTS OR SERVICES OR ANY UNDERTAKINGS, ACTS OR OMISSIONS RELATING THERETO. SELLER NEITHER ASSUMES NOR AUTHORIZES ANY PERSON TO ASSUME FOR IT ANY LIABILITY IN CONNECTION WITH THE SALE OF THIS PRODUCT OTHER THAN AS EXPRESSLY PROVIDED HEREIN.

COMPANY HISTORY	2
ENGINEERING & MANUFACTURING	3 & 42
DISTRIBUTION	43
TERMS & CONDITIONS	4

LIBERATOR ALUMINUM HAND TRUCKS

Popular Models	6
Build your Own Hand Truck	7-10
Handles & Frames	7
Noseplates & Wheels	8
Accessories	9-10
Features & Benefits	11
Convertible Hand Trucks	12-13
General Purpose Hand Trucks	14
Narrow Aisle Hand Trucks	15
Snack Food Carts	16-17
Fourth Wheel Attachment	18
Three-Way Hand Truck	19
Ice Cream Cart	20
Bakery Cart	20

BRAKE TRUCKS

Double Disc Brake Trucks	22
Double Disk Brake Kits	23
Tread Brake Trucks	24
Tread Brake Kits	25

HAND TRUCK DOCKBOARDS

ALUMINUM CURB RAMPS

WALKBOARDS

ALUMINUM PLATFORM TRUCKS

Formed Deck Platform Trucks	36-37
Welded Deck Platform Trucks	36-37

BEVERAGE INDUSTRY

Bulk Delivery System	26
Bulk Delivery Carts	27
Replacement Handles	27
Walkie Rider Cart	27
Bulk Delivery Cart Accessories	
Containment Curtain	28
Keg Hauler	28
Storage Rack	28
Curb Ramp	28

UPGRADE CURRENT FLEET

REPLACEMENT CART/PARTS

WAREHOUSE CARTS

FOOD SERVICE INDUSTRY

Brake Trucks	22-25
Snack Food Carts	16-17
Hand Truck Dockboards	17

DOCK EQUIPMENT

Aluminum Dockboard with Steel Bolt-On Curbs	31
Aluminum Dockboard with Welded Aluminum Curbs	32
How to Choose a Dockboard	33
Replacement Legs	33
Aluminum Truck Dockplates	34-35
Replacement Legs	35

Hand Truck Dockboards

WHEEL CHOCKS

RAMPS

Aluminum Curb Ramps	21
City Van Ramp	38
Perforated Deck Van Ramp	39
Wheel Ramps	41

PALLET DOLLIES

2 Year Warranty

Warranty covers failure of genuine B&P Manufacturing Liberator products due to defective material and/or workmanship. The 2 year warranty covers the following components: dockboards and plates, hand truck frames, frame components, handles, noseplates, noseplate brackets, axles, axle brackets, stairclimbers, stairclimber components, frame extensions, bulk delivery carts, walk ramps, and any other genuine B&P Manufacturing Liberator parts.

Liberator parts that are not covered under the 2 year warranty are: tires, inner tubes, wheels, bearings, casters, lift chains and parts other than genuine B&P Manufacturing Liberator parts. These items carry the standard warranty stated on page 4.

6 — **Liberator Aluminum Hand Truck** —

Popular Models



A11-B1-C6-D5-E1L-E52
Double grip handle, frame extension for 52" overall height, 18" x 9" extruded aluminum noseplate, 600 lb. capacity



A1-B1-C6-D5-E1L-E60-BTC
Standard loop handle, frame extension for 60" overall height, 18" x 9" extruded aluminum noseplate, tread brake technology for food service drivers, 600 lb capacity



A8-B1-C6-D5-E1L
"P" type handle, 60" overall height, beverage use, 600 lb capacity



A12-B5-CA2-D10-E1L-E9
Single pin handle, 52" overall height, cast, recessed heel noseplate, curved back frame, keg hook, fits U.S. sankey 1/2 barrel, 600 lb capacity



A11-B1-C6-D5-E1L-E60-BDC
Double grip handle, frame extension for 60" overall height, extruded aluminum noseplate, exclusive disc brake technology for food service applications, 600 lb capacity



A1-B10-CA1-D11
Standard loop handle, 50" overall height, cast, recessed heel noseplate, general purpose hand truck, 500 lb capacity.

Shown are a few popular models. Modular design allows you to build your own hand truck for your specific needs by selecting components on the following pages.

Handles and Frames

Choose (A) Handle, (B) Frame, (C) Nose Plate, (D) Wheels, and (E) Accessories to design your complete hand truck model - example: A1-B1-C1-D1-E1L

A Handles



A1, A2
Standard Loop
50" Overall
A2 with U Brace



A13, A14
Standard Loop
w/ Comfort Sleeve
50" Overall
A14 with U Brace



A37
Standard Loop
50" Overall
Square Top



A7, A10
Straight Loop
Vertical Grip at 52"
A7- 52" Overall
A10-52" Overall for
B4, B5 Frame



A8, A9, A25
Straight Loop
Vertical Grip at 52"
A8-60" Overall
A9-68" Overall
A25-60" Overall for
B4, B5 Frame



A11*
Standard Double Grip
48" Overall
Includes U Brace



A18, A19*
Welded Double Grip
A18- 52" Overall
A19- 60" Overall



A22*
Straight Double Grip
52" Overall



A40, A41, A42, A43*
Double Grip Handle, square top
A40- 52" Overall, 1 Crossmember
A41- 56" Overall, 2 Crossmembers
A42- 62" Overall, 2 Crossmembers
A43- 68" Overall, 3 Crossmembers



A15, A16
Straight Loop
Double Loop
Loop at 46"
A15- 55" Overall
A16- 60" Overall



A31S
55" Welded
Double Loop
(Straight)



A47
56" Welded
Double Loop
(No Flare)
w/ 1 Crossmember



A44
56" Welded
Double Loop
(Flared)
w/ 1 Crossmember



A21*
Straight Loop
60" Overall
Single Grip at 52"



A3, A4, A5, A6*
Straight Loop
Single Grip at 46"
A3- 52" Overall
A4- 55" Overall
A5- 60" Overall
A6- 68" Overall



A12*
Straight Loop
52" Overall
Single Grip

* Red Plastic Handle Grips are Standard - To Order handles with Black Ergo Grip add "E" to the Handle Part # (ie: A18E)

(Most common handles are shown here. A complete handle guide is available upon request)

B Frames




B1
Standard Straight
Back



B2
Lattice Back
With 1 Strap



B3
Lattice Back
With 2 Straps



B4
Curved Back
With 1 Strap
All Aluminum



B5
Curved Back
All Aluminum
Beer/Beverage Use



B7
Combination Back
2 Curved/
1 Straight




B8
Straight Back
55" Tall
No Logo Channel
Snack Truck
Use



B10
Straight Back
No Red Stripping

8 — Noseplate and Wheel Options —


C Noses




C1, C19
14" x 7.5"
Recessed Heel
C1- w/ Cutouts
C19- w/o Cutouts
Extruded Aluminum



CA1
14" x 7.5"
Cast, Recessed Heel
w/ Cutouts



C7
14" x 10.5"
Recessed Heel
w/ Cutouts
Extruded Aluminum



CA3
14" x 12"
Cast, Recessed Heel
w/ Cutouts



C2, C20
18" x 7.5"
Recessed Heel
C2- w/ Cutouts
C20- w/o cutouts
Extruded Aluminum



CA2
18" x 7.5"
Cast, Recessed Heel
w/ Cutouts



C15
18" x 10.5"
Recessed Heel
w/ Cutouts
Extruded Aluminum



C16, C12
14" x 7.5"
Front Mount
Extruded Aluminum
C16- w/o Cutouts
C12- w/ Cutouts



C4
14" x 9"
Front Mount
Extruded Aluminum



C8
16" x 12"
Front Mount
Extruded Aluminum



C17, C13
18" x 7.5"
Front Mount
Extruded Aluminum
C17- w/o Cutouts
C13- w/ Cutouts




C6, C26
18" x 9"
Front Mount
Extruded Aluminum
C6- w/o Cutouts
C26- w/Cutouts




C14
18" x 12"
Front Mount
Extruded Aluminum



C10
20" x 9"
Front Mount
Extruded Aluminum



C9
20" x 12"
Front Mount
Extruded Aluminum



C3
14" x 7.5"
Rear Mount
Extruded Aluminum



C5
18" x 7.5"
Rear Mount
Extruded Aluminum



C28, C29
C28 18" x 9"
C29 14" x 9"
Rear Mount
Steel
(C28 & C29 standard as
rear mount, can be front
mounted upon request)

D Wheels



D5
10" x 3.5"
4 Ply Pneumatic
2 pc. Steel Hub
Precision Bearings
600 lb. Capacity



D3F
10" x 3.5"
Pneumatic feel and performance.
Foam Filled - Can't Go Flat
600 lb. Capacity
THREE YEAR WARRANTY




D6
Carefree
10" x 3"
No Flat-Solid Foam
Won't Deteriorate
Non Marking
Made in the USA
600 lb. Capacity
Two Year Warranty



D10
10" x 2 1/8"
Balloon Cushion
Polyolefin Hub
Precision Bearings
600 lb. Capacity



D2
10" x 2.5"
Semi-Pneumatic
1 pc. Plastic Hub
500 lb. Capacity




D11
8" x 2 1/8"
Balloon Cushion
Polyolefin Hub
Precision Bearings
600 lb. Capacity



D14
Carefree
8" x 3"
Solid Foam-Won't Deteriorate
Non Marking
Made in the USA
600 lb. Capacity
Two Year Warranty
(For front mount and
cast noses only)



D9
8" x 2.5"
Pneumatic
2 pc. Steel Hub
500 lb. Capacity



D1
8" x 2"
High Performance
Dark Gray
Non Marking
Precision Bearing
600 lb. Capacity
(Use Short Axle)



D12
8" x 1 5/8"
Rubber on Aluminum
Offset Hub
600 lb. Capacity
(Use Short Axle)

E Accessories

Hand Truck Accessory Bag

Part #8218-001

Size: 12" w x 18" h x 2" d



Part #8218-002


Size: 12" w x 18" h x 3" d



Wheel Guards


Part #E8 - 7.38"

Part #E8L - 12"



Keg Hook

Part #E9



Extruded Aluminum Stairclimbers

Part #E1L

Revolutionary, high-strength extruded aluminum stairclimber with a 1/2" thick heavy-duty wear strip, 15" long.

Kit includes 2 stairclimbers plus hardware. **2 Year Warranty**



Cast Aluminum Stairclimber

Part #E1C


Fits Liberator and S-Series Trucks. Also fits most competitors trucks. Kit includes 2 stairclimbers plus hardware. **1 Year Warranty**



Steel Stairclimbers (10" wheel only)

Part #E28

Steel stairclimber attaches a full 28" up the frame. Lightweight, durable construction designed for the package delivery professional. **2 Year Warranty**



5/8" Steel Kick Bar For E1L Stairclimber

For use with 10" wheels Part #E46

For use with 8" wheels Part #E26



Pull Bar for E1L Stairclimber

Part #E29



Stretch Wrap Cutter

Part #SWC-1

20 per bag

Frame Extension Foam Sleeve
Part # 2002-E11

Durable Material Cover
Resists Tears
Longer Lasting Than Plain Foam Alternatives
Slides on Easily with a Spray of WD40 or Silicone Spray



Folding Noses



Tubular
E4F or E4R 44"
E5F or E5R 36"
E6F or E6R 30"
(110 lb. Capacity)




Full Channel Extruded
E2F or E2R 20"
E3F or E3R 30"
(300 lb. Capacity)

Order **F** For Use with Front Mount Nose Plates
Order **R** For Use with Recessed Heel or Rear Mount Nose Plates


Ergo Grip - Black
Part # 8017-003

Stronger and More Durable Than Other Vinyl Grips
More Resistant to Tearing Through
Made From Thicker Vinyl



Frame Extensions

Heavy-duty formed frame extensions
Part #
E45 45"
E52 52"
E55 55"
E60 60"
E68 68"



Fourth Wheel Attachment

Part # 2002-E37
Takes the load off the operator.
Lightweight design only weighs 8 lbs!
Latch keeps it up and out of the way when not in use.
600 lb. capacity
High Quality Casters - Smooth Rolling
Attaches easily to Liberator and S-Series Trucks
(Not Compatible with Stairclimbers or Convertibles)



Hand Truck Frame Wings

Provides additional support for large boxes and bags. Easy, bolt on assembly.
Adds 4" to hand truck width
Part #
E30 34" Long
E31 45" Long

(Not compatible with E1C or E28 Stairclimbers)

5/8" Steel Kick Bar/Pull Bar Kit
Part # E48



Kickbar Only-Part # E46
Pull Bar Only-Part # E47

Cylinder Attachment
Part # E43



Liberator Hand Truck

Features



Heavy Duty
Food Service Hand Truck

- Extruded aluminum construction absorbs impacts better than castings
- Weighs far less than steel
- Frames are rated at an actual 600 lbs capacity
- Crossmembers are attached with aircraft grade cherry rivets - Resists loosening over time
- Noseplates are constructed of non-cracking, high strength extruded aluminum
- Standard high tensile steel axle won't bend or fatigue under heavy loads
- Longer lasting extruded stairclimbers with heavy duty wear strips
- Lifetime warranty on wheel brackets



Curved Frame
Crossmembers
Constructed with
Extruded Aluminum
- Not Plastic
For Added Strength
and Durability

Heavy Duty Keg Truck

TWO YEAR WARRANTY



Heavy Duty Convertible



One Piece Solid Release Bar
Minimum Moving Parts for
Maximum Reliability




Balloon Cushion
Casters with Wing
Brake Standard on
One Wheel



Exclusive Tread Brake

OR

Double Disc Brake
Technology



12 ——— **Liberator Convertible Hand Trucks** ———

600 lb. Capacity Hand Truck

1200 lb. Capacity Platform Truck

Choose one of these popular models or build your own from components on page 13



“Senior”

Model A13-B81-C6-D5

- Loop Handle with Comfort Sleeve
- Heavy-Duty Frame with 5 Crossmembers
- 18” x 9” Solid Extruded Aluminum Nose Plate
- High Quality 10” x 3.5” 4 Ply Pneumatic Tires with Precision Bearings
- Crossbar with Comfort Sleeve



“Junior”

Model B70-C6-D5

- Double Grip Swing Arm
- Heavy-Duty Frame with 4 Crossmembers
- 18” x 9” Solid Extruded Aluminum Nose Plate
- High Quality 10” x 3.5” 4 Ply Pneumatic Tires with Precision Bearings



Guaranteed to be the best convertible you’ve ever used or send it back


Liberator Convertible Features:

- Thicker and stronger frame with heavy duty side channel reinforcements.
- Crossbars are four-sided tube with two sides ribbed for added strength.
- Crossbars are attached with individual aircraft-grade rivets at each corner providing better frame integrity.
- Heavy duty high tensile steel axle will not bow under maximum loads.
- Balloon cushion caster wheels provide better rollability (wing brake standard on one wheel).
- Our components can be used to upgrade other leading brands of hand trucks.

Two year warranty!!



Shown with Optional Solid Deck (E23L) and Frame Extension Wings (E32) adding 5” to overall deck width



- One piece solid release bar
- Simple design with minimal moving parts for maximum reliability
- Smoothest release action in the industry

SPECIFICATIONS	SR	JR
Overall width	20”	20”
Frame width	12”	12”
Overall length (platform mode)	56”	43”
Height as hand truck	61.5”	52”
Height as platform truck	46”	41”
Platform bed length	51.5”	38.25”
Platform height from floor	11”	11”
Balloon cushion swivel casters	5”x1.25”	5”x1.25”

Liberator Convertible Components and Replacement Parts

A Handles

B Frames

For Senior Models Only



A1
Standard Loop



A13
Standard Loop
w/ Comfort Sleeve



A26
Double Grip
w/ U Brace



B70
Jr. Double Grip



B75
Jr. Double Grip
2 Crossbars




B80
Standard




B81
High Capacity


C Noses




C1, C19
14" x 7.5"
Recessed Heel
C1 w/ Cutouts
C19 w/o Cutouts
Extruded Aluminum



CA1
14" x 7.5"
Cast, Recessed Heel
w/ Cutouts
500 lb. Capacity



C7
14" x 10.5"
Recessed Heel
w/ Cutouts
Extruded Aluminum




CA3
14" x 12"
Cast, Recessed Heel
w/ Cutouts
500 lb. Capacity



C2, C20
18" x 7.5"
Recessed Heel
C2 w/ cutouts
C20 w/o cutouts
Extruded Aluminum



CA2
18" x 7.5"
Cast, Recessed heel
w/ cutouts
500 lb. Capacity



C15
18" x 10.5"
Recessed Heel
w/ Cutouts
Extruded Aluminum




C16, C12
14" x 7.5"
Front Mount
Extruded Aluminum
C16- w/o Cutouts
C12- w/ Cutouts



C4
14" x 9"
Front Mount
Extruded Aluminum




C8
16" x 12"
Front Mount
Extruded Aluminum



C17, C13
18" x 7.5"
Front Mount
Extruded Aluminum
C17- w/o Cutouts
C13- w/ Cutouts



C6, C26
18" x 9"
Front Mount
Extruded Aluminum
C6- w/o Cutouts
C26- w/Cutouts



C14
18" x 12"
Front Mount
Extruded Aluminum



C10
20" x 9"
Front Mount
Extruded Aluminum




C9
20" x 12"
Front Mount
Extruded Aluminum



C28, C29
C28 18" x 9"
C29 14" x 9"
Rear Mount
Steel

(C28 & C29 standard as rear mount, can be front mounted upon request)

D Wheels



D10
10" x 2 1/8"
Balloon Cushion
Polyolefin Hub
600 lb. Capacity



D6
10" x 3"
Carefree
Solid Foam
600 lb. Capacity



D5
10" x 3.5"
4 Ply Pneumatic
2 pc. Steel Hub
600 lb. Capacity



D2
10" x 2.5"
Semi-pneumatic
1 pc. Plastic Hub
500 lb Capacity

E Accessories



Solid Decks
Removable Snap-On
or Permanent

E23L SR Snap On
E25L SR Permanent

E22L JR Snap On
E24L JR Permanent

E49 SR 18" Wide Permanent Deck



Folding Nose Extensions

Tubular
E5F, E5R 36"
E6F, E6R 30"



Full Channel Extruded
E2F, E2R 20"
E3F, E3R 30"



E32 Fixed Wings
(Senior Only)

F-for use with Front Mount Nose Plates
R-for use with Recessed Heel and Rear Mount Nose Plates

S-SERIES DIRECT REPLACEMENT HAND TRUCKS

500 lb Capacity - Two Year Warranty



S-500

- Loop handle
- Straight frame with standard crossmembers
- 14" x 7.5" cast noseplate, recessed heel with cutouts
- 8" balloon cushion wheels with precision bearings



S-502

- Loop handle
- Straight frame with standard crossmembers
- 14" x 7.5" cast noseplate, recessed heel with cutouts
- 10" balloon cushion wheels with precision bearings



S-503

- Double grip handle
- Straight frame with standard crossmembers
- 18" x 7.5" extruded aluminum, solid front mount noseplate
- 10" x 3.5" 4 ply pneumatic wheels with precision bearings

500 lb. Capacity Hand Truck
1,000 lb. Capacity Platform Truck
Two Year Warranty



SJR

- Convertible Junior
- 18" x 7.5" extruded aluminum, solid front mount noseplate
- 10" x 3.5" 4 ply pneumatic wheels with precision bearings



SSR

- Convertible Senior
- 18" x 7.5" extruded aluminum, solid front mount noseplate
- 10" x 3.5" 4 ply pneumatic wheels with precision bearings



Direct Replacement Series Components	
<u>HANDLES</u>	
A1	Single Loop
A11	Double Grip
<u>FRAMES</u>	
B10	Straight Back, No Logo Crossmember
B75	Junior Frame, Double Grip No Logo Crossmember
B80	Senior Frame, Standard No Logo Crossmember
<u>NOSE PLATES</u>	
CA1	14" x 7.5" Cast, Recessed Heel
C17	18" x 7.5" Extruded Aluminum
<u>WHEELS</u>	
D5	10" x 3.5" Pneumatic, 4 Ply, Precision Bearings
D10	10" Balloon Cushion, Poly Core
D11	8" Balloon Cushion, Poly Core

Add Optional Stairclimbers



EIL Extruded Aluminum



EIC Cast Aluminum

14" Wide and 18 lbs!

- Specially designed brackets move each wheel in 1.5" - only 14" wide with D11 wheels
- Fits all standard Liberator hand trucks, including curved back frames, front mount noses, cast noses, C28 & C29 rear mount steel noses, and all handles.
- Fits all 8" & 10" wheels, including short axle wheels (see below).
- Parts are interchangeable with most competitors.
- Optional stairclimbers are engineered from steel for long life (also available in extruded aluminum)
- Coke OFS compatible!
- Ideal for beverage distributors, provisions companies, liquor distributors- anyone delivering in tight areas.



A12-B10-CA1-D12-NA

-NA Indicates Narrow Aisle



C23 Coke OFS Compatible



-E40 Steel Stairclimber for Narrow Aisle Hand Truck



-E44 Extruded Aluminum Stairclimber for Narrow Aisle Hand Truck



Part Description

(NA Indicates Narrow Aisle Component)

Part

LH Wheel Bracket NA	7507-001
RH Wheel Bracket NA	7507-002
Long Axle, Narrow Aisle	2002-272
Short Axle, Narrow Aisle	2002-273
Stairclimber (Pair), Narrow Aisle Steel	2002-E40
Stairclimber, Extruded Aluminum, Narrow Aisle	2002-E44
Completion Pack, Long Axle NA	2002-333
Completion Pack, Short Axle NA	2002-334

Developed for the Snack Food Delivery Professional



Shown with optional 51" skids

- Reduce your number of trips
- Lightweight aluminum construction - reduce fatigue
- Modular design allows perfect fit for individual drivers
- Extra long skids allow truck to slide easily out of the delivery vehicle
- Optional Folding nose for bulky packages (44" shown)
- Two Year Warranty



Tubular Folding Nose Extension

36" **E5F/E5R**

44" **E4F/E4R**

F for use with Front Mount Nose

R for use with Rear Mount or Recessed Nose

110 lb. Capacity


A8-B8-CA1-D11-E19-E4R

(Height with A8 Handle As Shown 75 1/2")


If adding skids order

-E19 for use with 8" wheels

-E20 for use with 10" wheels



Most popular models and handle styles are shown here, but our modular design allows your choice of any B&P handles, noseplates or wheels



D10

10" x 2 1/8"
Balloon Cushion
Polyolefin Hub
600 lb Capacity



D11

8" x 2 1/8"
Balloon Cushion
Polyolefin Hub
600 lb. Capacity



D5

10" x 3.5"
4 Ply Pneumatic
2 pc. Steel Hub
600 lb. Capacity



D6

Carefree
10" x 3"
No Flat
Solid Foam
600 lb. Capacity



D14

Carefree
8" x 3"
No Flat
Solid Foam
600 lb. Capacity



D1

8" x 2"
High Performance
Dark Gray
Non-Marking
600 lb. Capacity



D9

8" x 2.5"
Pneumatic
2 pc. Steel Hub
500 lb. Capacity

HTA-10 Folding Snack Truck



- Lightweight, high capacity design
- 66" bed length allows you to carry large boxes of chips, pretzels, etc.
- 36" folding nose keeps boxes in place, yet folds up for transportation and storage
- Latches keep both the handle and folding nose in the upright position Standard with 14" x 7 1/2" cast noseplate (CA1) and 8" balloon cushion wheels (D11)
- 5" x 1 1/4" swivel stem casters provide a smooth ride and long life

SPECIFICATIONS

Overall Height	73"
Width (at nose plate CA1)	14"
Bed Length	66"
Handle Height	38"
Folding Nose Length	36"
Folding Nose Height	46"
Weight (w/ D11)	35 lb
Capacity (folding nose)	80 lb
Capacity (4 wheel)	200 lb

Noseplate Options

14" x 7 1/2" Cast/Recessed Heel Nose Standard	CA1
18" x 7 1/2" Cast/Recessed Heel	CA2
14" x 12" Cast/Recessed Heel	CA3
14" x 7 1/2" Extruded Aluminum/Recessed Heel	C1
18" x 7 1/2" Extruded Aluminum/Recessed Heel	C2

Wheel Options

8" Balloon Cushion Standard	D11
8" Aluminum Core Mold on Rubber	D12
8" Pneumatic	D9

9" Apron



11 deg. bend

APRON HAND TRUCK DOCKBOARDS

- A lightweight solution for dock to truck/truck to truck applications
- Features our exclusive punched design providing excellent traction while preventing buildup of mud, slush, ice or debris
- Curbs provide an increased margin of safety
- Steel bolt-on legs



Model #	Size W x L	Capacity	Leg Length	Max Height Diff	Weight
AHTD-3036	30" x 36"	800 lbs	7"	5"	27 lbs
AHTD-3048	30" x 48"	800 lbs	9"	7"	35 lbs

- 4th wheel attachment takes the load off the operator
- Latch keeps the 4th wheel up and out of the way when not in use
- Lightweight design weighs only 8 lbs!
- 600 lb capacity
- Attaches to Liberator and S-Series Trucks
- Optional latch system locks the 4th wheel to prevent accidental closing (2002-E37L)
- Smooth rolling TPR casters


(Not compatible with stair climbers or convertible trucks.)




Optional cylinder attachment carries large tanks. (2002-E43)



Optional wings provide additional support for large boxes.(2002-E30)



Latch keeps 4th wheel up when not in use.



Latch and pin system keeps the 4th wheel extended (2002-E37L)

— “Three Way” Liberator Hand Truck — 19

Engineered for Bottled Water, Ice and Other Delivery Professionals



Truck Locks Securely in Any of the Three Positions for Safety

- Standard with 18” x 7.5” cast noseplate and 10” pneumatic tires with precision bearings
- Integral 27” folding nose for large loads stores out of the way when not in use

Other noseplates and wheels available
Consult factory for details

Specifications

Height in 2 wheel position	52”
Height in 4 wheel position	42”
Deck Area	51” x 12”
Deck Height	11”
Capacity in 2 wheel position	600 lb.
Capacity in 4 wheel position	900 lb.
Weight (as shown)	48 lb.



B60 CA2 D5

New Design!**IC-1**

- Riveted construction for durability
- 8" balloon cushion wheel (D11) standard
- 18" slatted nose standard
- Aircraft grade cables support nose
- Engineered housing supports axle and allows use of stairclimbers



Shown with optional stairclimbers
Model # IC-1-E1L

Wheel Options

- D11 8" balloon cushion standard
D1 8" tpr, dark gray non-marking
D9 8" pneumatic
D12 8" mold-on rubber, aluminum core

Noseplate Options

- 18" slatted nose standard
18S 18" solid nose
24SL 24" slatted nose
24S 24" solid

Bakery Cart

- Solid back and large noseplate to handle bulky baked goods, trays and boxes
- Skids allow cart to slide easily up and down truck beds and loading ramps

- Width 20"
Height 52"
Noseplate (C10) 20"W x 9"D

Wheel Options

- D5 shown 10" Pneumatic
D10 10" Balloon Cushion
D11 8" Balloon Cushion

B9-C10-D5-E15-E18 Shown with D5 wheels and optional Frame Extension (E15) and E18 skids for 10" wheels
(Note: Use E14 skids with 8" wheels, E18 skids with 10" wheels)

Totally New Curb Ramp Design Makes All Other Curb Ramps OBSOLETE!



- Our exclusive process punches holes in the material, then raises the edges of the cutouts for superior traction
- Exceptionally lightweight
- Won't collect ice, mud, snow, or debris
- Handle slot doubles as a stop

Part #	Capacity	W" x L"	Weight
CRP2618	750 lb	26 x 18	8 lb
CRP2727	750 lb	27 x 27	13 lb
CRP2736	750 lb	27 x 36	17.5 lb
CRP3030	750 lb	30 x 30	15 lb
CRP2745	500 lb	27 x 45	22 lb




- Wedge design curb ramp features the same punched design for traction
- Sides folded down keep the ramp in place and allows more usable width
- 600 lb. capacity in a curb ramp weighing only 6 lb (22x24)

Part #	Capacity	W" x L"	Weight
CRW2224	600 lb	22 x 24	6 lb
CRW2724	750 lb	27 x 24	12 lb


WALKBOARDS

- Lightweight, one piece design is resistant to bending and fatigue
- Ideal for spanning between truck and loading dock
- Punched design won't collect ice, mud, snow, or debris

Part #	Capacity	W" x L"	Weight
LWB2448	750 lb	24 x 48	39 lb



Formed profile provides strength without adding weight



Bolt on hooks secure walkboard to truck bed

Heavy Duty Food Service Trucks

- Automotive style, dual disc brakes provide the ultimate in driver control and safety
- Total stopping power for the heaviest loads
- Braking is not affected by rain, snow, mud, or slush
- New cable actuated design is virtually maintenance free and provides equal stopping power to both wheels for consistent braking action with no pulling left or right
- Available with pneumatic tires, foam tires, and our slime treated pneumatic tires for the ultimate in flat-free performance

Available in most handle styles

Order trucks complete, or kits are available to install on Liberator hand trucks.



A4-B1-C6-D5-E1L-E13-BDC



A47-B1-C6-D5-BDC

E29 Pull Bar
Gets the hand truck out from under loads and makes it easier to lift into trailer

E13 Kick Bar
Make easy work of kicking loads back



A8-B1-C6-D5-E1L-E13-E29-E31-BDC



A43-B2-C6-D5-E1L-E13-BDC




A6-B1-C6-D5-E1L-E13-BDC

See complete list of components to build your own hand truck on page 7-10

Add Our Double Disc Brake Kit to Liberator Hand Trucks

- Our kits have everything you need to upgrade your Liberator hand truck to the ultimate brake truck - Kits include handles where necessary, all levers, cables, hardware, and a detailed installation guide
- Choose your kit below based on your specific handle and wheel combination
- New lever/cable system eliminates T-rods and provides excellent leverage in an ergonomic design
- Double disc design provides load control while allowing wheels to turn independently



Fits A1, A2, A13 and A14
(Handle sold separately)

D5 Tire 2005-BDCA1D5
D5S Tire 2005-BDCA1D5S
D6 Tire 2005-BDCA1D6



A3, A4, A5 and A6
(Includes Handle)

A3
D5 Tire 2005-BDCA3D5
D5S Tire 2005-BDCA3D5S
D6 Tire 2005-BDCA3D6

A4
D5 Tire 2005-BDCA4D5
D5S Tire 2005-BDCA4D5S
D6 Tire 2005-BDCA4D6

A5
D5 Tire 2005-BDCA5D5
D5S Tire 2005-BDCA5D5S
D6 Tire 2005-BDCA5D6

A6
D5 Tire 2005-BDCA6D5
D5S Tire 2005-BDCA6D5S
D6 Tire 2005-BDCA6D6



Fits A11, A40, A41, A42, A43, A44
(Handle sold separately)

D5 Tire 2005-BDCA11D5
D5S Tire 2005-BDCA11D5S
D6 Tire 2005-BDCA11D6



A12 and A21
(Includes Handle)

A12
D5 Tire 2005-BDCA12D5
D5S Tire 2005-BDCA12D5S
D6 Tire 2005-BDCA12D6

A21
D5 Tire 2005-BDCA21D5
D5S Tire 2005-BDCA21D5S
D6 Tire 2005-BDCA21D6



A7, A8 and A9
(Includes Handle)

A7
D5 Tire 2005-BDCA7D5
D5S Tire 2005-BDCA7D5S
D6 Tire 2005-BDCA7D6

A8
D5 Tire 2005-BDCA7D5
D5S Tire 2005-BDCA7D5S
D6 Tire 2005-BDCA7D6

A9
D5 Tire 2005-BDCA7D5
D5S Tire 2005-BDCA7D5S
D6 Tire 2005-BDCA7D6

Reduce risk of fatigue and injury!

- 600 lb. capacity (with specified wheels)
- 4 sided frame crossmembers for rigidity
- Attached with 700 pound rated aircraft rivets
- Exclusive logo channel - Provides identity and unsurpassed fatigue resistance
- Non cracking, high strength extruded aluminum noseplates
- High tensile steel axle - standard
- Extruded axle brackets for strength and impact resistance
- Extruded - not cast - stairclimbers

BACKED BY A TWO YEAR WARRANTY!



"We have sold and serviced brake trucks for years and find that B&P works the best and requires virtually no maintenance"

-Southern Distributor



Brake shoes contact the front of the wheel, not the top or back. This prevents the possibility of locking up due to low tire pressure. Angled raking surface provides more friction on the tire than paddle designs, increasing stopping power.



Our unique lightweight tread brake design applies even pressure to both wheels assuring load control even in wet conditions. New cable design eliminates T rods and provides excellent leverage in an ergonomically correct design. Modular design allows for easy repair of damaged components.




A1-B1-C8-D5-BTC

A5-B1-C8-D5-BTC

A8-B1-C8-D5-BTC

We Have Taken Our Proven Tread Brake System and **Made it Better!**

- We have engineered a lever and cable system for the handles which provides more leverage than previous systems and offers a more ergonomically correct design.
- The lower pull bar has been upgraded to eliminate the clevis. The eye bolt goes directly through the pull bar, allowing more adjustment than before.
- Previous tread brake systems are easily upgraded.



Fits A1, A2, A13 and A14
(Handle sold separately)

Part #2005-BTCA1



Fits A11, A40, A41, A42, A43, A44

(Handle sold separately)

Part #2005-BTCA11



A3, A4, A5 and A6
(Includes Handle)

Part #2005-BTCA3

Part #2005-BTCA4

Part #2005-BTCA5

Part #2005-BTCA6



A12 and A21
(Includes Handle)

Part #2005-BTCA12

Part #2005-BTCA21



A7, A8, and A9
(Includes handle)

Part #2005-BTCA7

Part #2005-BTCA8

Part #2005-BTCA9



- Pre-load by account at the warehouse - carry only what you need, reducing fuel costs
- Eliminate picking on the street - Keeps product out of the elements and reduces the risk of injuries associated with bay trucks
- Average 40 cases per cart vs 10 for a hand truck - Reduce the number of trips by up to 400%
- Straight trucks instead of bay trucks - lower initial cost and lower maintenance costs
- Faster check-in time - Reduce account service times by up to 50% increasing customer satisfaction



TWO YEAR WARRANTY

- Increase Efficiency
- Reduce Risk of Injuries
- Lower Maintenance Costs
- Better Driver Retention

INCREASED BOTTOM LINE!



THE BEST BUILT, BEST BACKED CART!



- Heavy duty deck with double bracing is a full 1/8" thick
- Formed, one piece deck won't curl like welded deck designs
- Monolithic design virtually eliminates deck twisting and failure due to fatigue
- Fully welded handle pockets - Stronger and longer lasting
- Handles are round, heavy wall aluminum for excellent resistance to bending and breaking
- Handles stay in place while in use, yet easily removable for loading/unloading

EXCLUSIVE CENTER BRAKE SYSTEM



- Brake system locks both center wheels for loading/unloading and transportation
- Actuated from either end or either side
- No unexpected cart movement

*Free Freight Program does not apply to Bulk Delivery Carts.

Optional Removable Shelf (200 lb. capacity)



FHE-1

- 18" x 60" deck
- Two handles with 2 crossbars, 1 vertical strap, and buttons for containment curtain (part # each handle 2025-134)
- 8" x 2" Urethane center wheels (part #8057-114)
- 6" x 2" TPR square tread swivel casters (part #8057-038)
- 1200 lbs capacity
- Weight 90 lbs

TO ORDER WITH BRAKE OPTION
ORDER **FHE-1B** Weight 97 lbs

FHE-6 Walkie Rider Cart




Pictured with #207 Handles


- 18" x 60" deck
- Allows 2 carts to sit side by side on walkie riders or forklifts
- Steel Understructure
- Accepts forks up to 10 1/2" wide
- Requires only 7" between forks
- 1200 lbs capacity
- Weight 90 lbs

*Walkie Rider Not available with brake

Standard Understructure



Walkie Rider Understructure




HANDLE OPTIONS/REPLACEMENT HANDLES

2 STANDARD ON ABOVE CARTS
(#204 Handle Option)

2 Crossbars/1 Vertical Strap, 3/16" thick
Buttons for containment curtain
(To order replacements order
Part # 2025-134)


(If buttons for containment
curtain are not required order
part number 2025-103)



ALSO AVAILABLE:
(Order #207 Handle Option)

2 Crossbars/1 Vertical Strap,
Buttons for containment curtain
(To order replacements order
Part # 2025-130)

(If buttons for containment
curtain are not required order
part number 2025-131)



28 — Bulk Delivery Cart Accessories —



CANVAS
Part # 2025-503




MESH
Part # 2025-505

- **Product Containment Curtain** that works!
- Available in canvas (part # 2025-503) and mesh (part # 2025-505)
- Eliminate costly and unsightly stretch wrap
- Keeps load secure
- Straps don't drag on the ground
- Steel strap clips won't break



Liberator Keg Hauler
Part # KEG-1

- Hauls 6 full half barrels!
 - Lightweight extruded tubular aluminum design.
 - Locking tabs keep KEG-1 in place yet removes easily with integrated handles
- Fits 60" and 61" carts (18" width)



Stackable
Bulk Delivery Cart Storage Rack
Part # 2026-001

- Maximize Warehouse Space - Cart rack has a capacity to hold 14 carts and 28 handles
 - Aluminum Construction - Makes the cart rack strong and last long
 - Convenient way to store multiple bulk delivery carts in one place with the ability to stack 3 cart racks high
- 51" Deep, 96" Wide, 68 1/2" High
Weight 210 lbs empty
Max Height 207" (3 High Requires 20 Ft. Ceiling Minimum)

Part # NCR2745

Curb Ramp for use with Bulk Delivery Cart
1/4" Smooth Plate with Non-Skid Tape
27" Wide x 45" Long
1400 Lb Capacity
Weight 34 Lb



We are the experts in bulk delivery!

Call one of our product experts to design a cart to suit your specific application.

Universal Bulk Delivery Square Pocket Design



Square Handle Fits Competitor Models

From Casters to Complete Carts, B & P Manufacturing Offers the Guaranteed Best in Bulk Delivery Systems

FHM-1

- 18"x60" smooth deck, square pockets
- 8" rigid urethane center casters (P/N 8057-007)
- 8" TPR swivel casters (P/N 8057-017)




- Replace casters or upgrade to our exclusive heavy duty understructure.




- Product containment curtain for 60" carts. Replace torn curtains with our unique design, providing more durable metal clips.
- Available in Mesh (P/N 2025-506) or Solid Canvas (P/N 2025-507)

NEW STRONGER HANDLE



- Replacement handles feature a more ergonomic handle design that reduces driver hand fatigue. (P/N 2025-165)



- Replacement decks feature our more durable formed design.
- Square pockets accept competitor handles. (P/N FHS-1860S)

With Heavy Duty Understructure - **FHS-1**

With Heavy Duty Understructure and Brake - **FHS-1B**

Model shown FHE-2460-217-HD10-SH with square handles and shelf option



- 24" wide x 60" long deck
- Two handles with two crossbars and one vertical strap
- 8" x 2" urethane center wheels (part # 8057-114)
- 6" x 2" TPR square tread swivel casters (part # 8057-038)

Capacity 1,200 lb

- Optional removable shelf (add -SH to model #)
Capacity 200 lb
- Optional center brake (add -CB to model #)

Retail Beverage Pre-Cool Cart Model # MAC-12

- Keeps product cold in walk in coolers
- Save precious cooler space
- Easily transports to point of sale coolers
- Reduce customer complaints due to warm product
- Eliminate stock rotation

24" Wide x 58.88" Overall Length x 61" Overall Height
8" x 2" TPR Center Wheels (p/n 8057-018)
6" x 2" TPR Swivel Casters (p/n 8057-038)


750 lb capacity - Shelf capacity 250 lb



- Tilt design allows easy maneuvering in tight places
Spins on it's own axis
- Folds flat for compact storage, reducing shipping costs
- Lightweight design is easily transported
- Heavy duty understructure for maximum durability
- Non marking wheels for in store use
- Modular construction for easy replacement of damaged components
- Adjustable/removable shelf to accommodate a variety of products
- Adjustable handle height



Aluminum Dockboard with Steel Curbs



- **Lightweight Aluminum Deck With Safety Treadplate Surface**
- **Heavy Duty Bolt-On Steel Curbs** for strength. Helps prevent run off. High visibility orange for safety.
- **Beveled Edges** provide smooth entry and exit.
- **Engineered Bend** keeps the edges of the dockboard flush with both dock and truck.
- **Heavy Duty Steel Bolt-On Legs** can be reversed for refrigerated applications.

Industry Exclusive Two Year Warranty

SPECIFICATIONS			10,000 LB CAPACITY 3/8" Aluminum, 4" High Steel Curbs			15,000 LB CAPACITY 1/2" Aluminum, 4" High Steel Curbs		
Size (WxL)	Max Height Difference	Leg Length	Cap. (Lbs)	Model #	Wt (Lbs)	Cap. (Lbs)	Model #	Wt (Lbs)
60" x 36"	5"	7"	10,000	ADS10-6036	126	15,000	ADS15-6036	153
60" x 48"	7"	9"	10,000	ADS10-6048	169	15,000	ADS15-6048	204
60" x 60"	10"	12"	10,000	ADS10-6060	211	15,000	ADS15-6060	255
60" x 72"	12"	18"	10,000	ADS10-6072	261	15,000	ADS15-6072	314
72" x 36"	5"	7"	10,000	ADS10-7236	174	15,000	ADS15-7236	193
72" x 48"	7"	9"	10,000	ADS10-7248	190	15,000	ADS15-7248	255
72" x 60"	10"	12"	10,000	ADS10-7260	237	15,000	ADS15-7260	322
78" x 36"	5"	7"				15,000	ADS15-7836	178
78" x 48"	7"	9"				15,000	ADS15-7848	238
78" x 60"	10"	12"				15,000	ADS15-7860	297
78" x 72"	12"	18"				15,000	ADS15-7872	357

"Quick Ship" available on all sizes

Accessories

Lifting Chains


Heavy duty chains for forklift moving of dockboards

Quickly and easily attached onto the dockboard curb with heavy duty steel hooks

(Recommended for boards 10,000 lb capacity and up)

*See page 33 for replacement leg sizes and part numbers

Aluminum Dockboard with Welded Aluminum Curbs



- FULLY WELDED ALUMINUM CURBS FOR MAXIMUM STRENGTH AND DURABILITY
- STEEL BOLT-ON LEGS
- INDUSTRY EXCLUSIVE TWO YEAR WARRANTY
- QUICK-SHIP AVAILABILITY ON POPULAR SIZES

SPECIFICATIONS			5,000-7,000 LB CAPACITY 5/16" Aluminum, 3" High Curb (if noted with * plate is 3/8" Alum)			10,000 LB CAPACITY 3/8" Aluminum, 3.5" High Curb			12,000-15,000 LB CAPACITY 3/8" Aluminum, 4" High Curb			12,000-17,000 LB CAPACITY 1/2" Aluminum, 4" High Curb		
Size (W x L)	Max Height Difference	Leg Length	Cap. (Lbs)	Model #	Wt (Lbs)	Cap. (Lbs)	Model #	Wt (Lbs)	Cap. (Lbs.)	Model #	Wt (Lbs)	Cap. (Lbs)	Model #	Wt (Lbs)
48"x36"	5"	7"	7,000	L7-4836	80	10,000	L10-4836	97						
48"x48"	7"	9"	7,000	L7-4848	107	10,000	L10-4848	130						
48"x60"	10"	12"	7,000	L7-4860	133	10,000	L10-4860	162						
60"x36"	5"	7"	7,000	L7-6036	93	10,000	L10-6036	113	15,000	L15-6036	120	17,000	L17-6036	146
60"x48"	7"	9"	7,000	L7-6048	124	10,000	L10-6048	151	15,000	L15-6048	160	17,000	L17-6048	195
60"x60"	10"	12"	7,000	L7-6060*	155	10,000	L10-6060	188	15,000	L15-6060	200	17,000	L17-6060	244
60"x72"	12"	18"	5,000	L5-6072*	193				12,000	L12-6072	248	15,000	L15-6072	300
72"x36"	5"	7"	5,000	L5-7236	106				12,000	L12-7236	136	15,000	L15-7236	167
72"x48"	7"	9"	5,000	L5-7248	141				12,000	L12-7248	181	15,000	L15-7248	223
72"x60"	10"	12"	5,000	L5-7260*	177				12,000	L12-7260	226	15,000	L15-7260	279
72"x72"	12"	18"										12,000	L12-7272	342

Popular sizes in bold print available for "Quick Ship" upon request

Accessories

Handles

Add lift handles for easy movement
(Only available on 5,000 and 7,000 capacity boards)

Lifting Chains

Heavy duty chains for forklift moving of dockboards

Quickly and easily attached onto the dockboard curb with heavy duty steel hooks

(Recommended for boards 10,000 lb capacity and up)

How to choose a Dockboard:

Step 1: Determine capacity - add the weight of the forklift and the weight of the maximum load to be carried

Step 2: Determine Width - The width of the dockboard should be at least 18 inches wider than your widest equipment passing over the board. Remember, safety curbs take up 6 inches of usable width.


Example: A 60 inch dockboard has 54 inches of usable space.

Step 3: Determine Length - You need to know the maximum difference between the height of the dock and the height of the highest truck bed.

1. Max. Truck Height	
2. Minus Dock Height	-
3. Equals Height Difference	=

Using the chart below, determine the length of the board you need. An 11 degree bend is standard. Example: If the maximum height difference is 7 inches, a board at least 48 inches long is required.


SLOPE ANGLE	MAXIMUM HEIGHT DIFFERENCE (INCHES)																	
	1	2	3	4	5	5.5	6	7	8	8.5	9	10	11	12	13	14	15	16
11 DEG. STANDARD				30	36		42	48		54		60	66	72	78	84	90	96



To Order Replacement Legs:

BOARD LENGTH	LEG LENGTH	TO ORDER 1 LEG (NO HARDWARE)	TO ORDER A PAIR OF LEGS (INCLUDES HARDWARE)
36 inches	7 inch	P/N 8062-001	P/N 3500-L7
48 inches	9 inch	P/N 8062-002	P/N 3500-L9
60 inches	12 inch	P/N 8062-003	P/N 3500-L12
72 inches	18 inch	P/N 8062-004	P/N 3500-L18

Best Selling Dockplates in America



DOCKPLATES STANDARD WITH 2 HANDLES - SUBSTITUTE HAND SLOTS AT NO EXTRA CHARGE

- **High-Traction, Safety Treadplate Surface** gives positive traction for equipment and safe footing for personnel.
- **Bolt-On Legs/Handles** allow for quick field repair and ease of moving/lifting - Easily reversed for refrigerated trucks.
- **Beveled Edges** provide smooth entry and exit.
- **Engineered Bend** keeps the edges of the dock plate flush with both dock and truck.
- **Safety Yellow Tape** on edges for low light visibility

Two Year Warranty


How To Select The Correct Dockplate: NON MOTORIZED USE ONLY!

Step 1: Determine Width - add 12" to the widest load that will go over the plate

Step 2: Determine Capacity - weight of pallet jack + maximum weight of items carried + operator weight

If the maximum load is within 50 pounds of the stated capacity, select the next highest capacity.

Step 3: Determine Length - required length is determined by height difference between dock and truck floor



	MAXIMUM HEIGHT DIFFERENCE IN INCHES																	
SLOPE ANGLE	1	2	3	4	5	5.5	6	7	8	8.5	9	10	11	12	13	14	15	16
11 DEG. STANDARD				30	36		42	48		54		60	66	72	79	84	90	96

A Note About Capacities

All B&P dockplates are rated at actual capacities, per Aluminum Industry Association standards. Some other companies rate capacities with a formula that considers the fact that only two wheels of the four wheel vehicle will be on the plate at one time. This can artificially overstate the capacities of the plates, creating a potentially dangerous situation. We state our capacities as actual, giving you an extra margin of safety.

Dockplates are standard with 2 handles - Order with hand slots at no additional charge

SPECIFICATIONS			EL SERIES 5/16" Plate			E SERIES 3/8" Plate			EH SERIES 1/2" Plate		
Size (w x l)	Max Ht. Diff (In)	Leg Length	Cap. (Lbs)	Model #	Weight (Lbs)	Cap. (Lbs)	Model #	Weight (Lbs)	Cap. (Lbs)	Model #	Weight (Lbs)
30x24	3	7	2196	EL-3024	42	3000	E-3024	46	5200	EH-3424	55
30x30	4	7	1757	EL-3030	47	2300	E-3030	53	4100	EH-3030	64
30x36	5	7	1464	EL-3036	53	1800	E-3036	60	3500	EH-3036	72
30x48	7	9	1098	EL-3048	68	1400	E-3048	76	2600	EH-3048	94
36x24	3	7	2636	EL-3624	46	3600	E-3624	51	6200	EH-3624	62
36x30	4	7	2108	EL-3630	53	3000	E-3630	58	5100	EH-3630	72
36x36	5	7	1757	EL-3636	59	2500	E-3636	68	4300	EH-3636	82
36x48	7	9	1318	EL-3648	76	1900	E-3648	87	3000	EH-3648	108
42x24	3	7	3075	EL-4224	51	4300	E-4224	57	7200	EH-4224	68
42x30	4	7	2460	EL-4230	58	3300	E-4230	64	5900	EH-4230	81
42x48	7	9	1537	EL-4248	85	2100	E-4248	96	3500	EH-4248	123
48x24	3	7	3514	EL-4824	55	5200	E-4824	62	8200	EH-4824	75
48x30	4	7	2811	EL-4830	64	4100	E-4830	72	6300	EH-4830	90
48x36	5	7	2343	EL-4836	72	3500	E-4836	83	5300	EH-4836	104
48x42	6	9	2008	EL-4842	85	3000	E-4842	96	4300	EH-4842	122
48x48	7	9	1757	EL-4848	94	2600	E-4848	107	3800	EH-4848	137
48x60	10	12				1800	E-4860	132	2900	EH-4860	168
60x24	3	7	4393	EL-6024	64	5700	E-6024	71	10000	EH-6024	90
60x30	4	7	3514	EL-6030	75	4600	E-6030	85	7800	EH-6030	108
60x36	5	7	2928	EL-6036	85	4100	E-6036	98	6600	EH-6036	125
60x42	6	9	2510	EL-6042	100	3500	E-6042	115	5500	EH-6042	148
60x48	7	9	2196	EL-6048	111	2900	E-6048	129	4800	EH-6048	164
60x60	10	12				2000	E-6060	160	3700	EH-6060	203
72x30	4	7	4217	EL-7230	85	5400	E-7230	98	9500	EH-7230	125
72x36	5	7	3514	EL-7236	99	4300	E-7236	118	7800	EH-7236	145
72x48	7	9	2636	EL-7248	129	3400	E-7248	151	5900	EH-7248	191

*Popular sizes in bold print available for "Quick Ship" upon request

TO ORDER REPLACEMENT LEGS:

Leg & Handle Assy (pair w/hardware)

- 7" Legs **Part #3500-L7H2**
- 9" Legs **Part #3500-L9H2**
- 12" Legs **Part #3500-L12H2**

1 Leg w/Handle (does not include hardware)

- 7" Leg w/Handle LH **Part #8220-001**
- 7" Leg w/Handle RH **Part #8220-002**
- 9" Leg w/Handle LH **Part #8220-003**
- 9" Leg w/Handle RH **Part #8220-004**
- 12" Leg w/Handle LH **Part #8220-005**
- 12" Leg w/Handle RH **Part #8220-006**

For Plates with Hand Slots (pair of Legs w/hardware)

- 7" Legs **Part #3500-L7**
- 9" Legs **Part #3500-L9**
- 12" Legs **Part #3500-L12**

1 Leg Only - No Handle (does not include hardware)

- 7" Leg Only/No Handle **Part #8062-001**
- 9" Leg Only/No Handle **Part #8062-002**
- 12" Leg Only/No Handle **Part #8062-003**

Leg Hardware Kit **P/N 3500-H1** - includes 8 carriage bolts and 8 nylock lock nuts

AVAILABLE IN FORMED DECK OR WELDED DECK DESIGN***BOTH FEATURING A TWO YEAR WARRANTY!*****EXCLUSIVE FORMED DECK DESIGN**

- Strong and lightweight
- Design eliminates warping and waving
- High capacity
- Tread plate or smooth plate deck
- Handle and caster options for most applications



PTF-3048S-150-850
 30" x 48" smooth plate deck
 one standard #150 handle
 8"x2" TPR casters
 (2 swivel, 2 rigid)
 2,000 lb capacity



PTF-3048T-150-850
 30" x 48" tread plate deck
 one standard #150 handle
 8"x2" TPR casters
 (2 swivel, 2 rigid)
 2,000 lb capacity


HEAVY DUTY WELDED DECK DESIGN

Industry exclusive side rails actually lock the deck in to provide strength and resistance to twisting and deck curling. The side rail also allows field installation of the protective bumper and deck carpeting. These features, combined with our standard setting heavy duty understructure, make this the best platform truck on the market, hands down.



PT-3060T-150-650
 30" x 60" tread plate deck
 one standard #150 handle
 6"x2" TPR casters
 (2 swivel, 2 rigid)
 1,500 lb capacity
 (2,000 lb capacity with
 #850 casters)

Available with Tread Plate,
 Smooth Plate, or Carpeted Decks



Full protective bumper available on all welded models in standard black or non-marking gray.



Shown with Full Protective Bumper
 and Carpeted Deck

PT-3060S-150-850-C-310
 30" x 60" smooth plate deck
 one standard #150 handle
 8"x2" TPR casters
 (2 swivel, 2 rigid)
 carpeted deck
 full perimeter gray bumper
 2,000 lb capacity

FORMED DECK WITH ONE #150 OPEN HANDLE

DECK SIZE	TREAD PLATE DECK	SMOOTH PLATE DECK
W" X L"	MODEL #	MODEL #
24 x 36	PTF-2436T-150	PTF-2436S-150
24 x 48	PTF-2448T-150	PTF-2448S-150
30 x 48	PTF-3048T-150	PTF-3048S-150
30 x 60	PTF-3060T-150	PTF-3060S-150
30 x 72	PTF-3072T-150	PTF-3072S-150
36 x 48	PTF-3648T-150	PTF-3648S-150

OPTIONAL HANDLES



#155 Handle
One Strap



#160 Handle
Two Straps



#165 Handle
18" Panel

WELDED DECK WITH ONE #150 OPEN HANDLE

DECK SIZE	TREAD PLATE DECK	SMOOTH PLATE DECK
W" X L"	MODEL #	MODEL #
24 x 36	PT-2436T-150	PT-2436S-150
24 x 48	PT-2448T-150	PT-2448S-150
24 x 60	PT-2460T-150	PT-2460S-150
30 x 48	PT-3048T-150	PT-3048S-150
30 x 60	PT-3060T-150	PT-3060S-150
30 x 72	PT-3072T-150	PT-3072S-150
36 x 48	PT-3648T-150	PT-3648S-150
36 x 60	PT-3660T-150	PT-3660S-150
36 x 72	PT-3672T-150	PT-3672S-150

CASTER OPTIONS (2 RIGID, 2 SWIVEL)

TPR Non-Marking Casters
The Best High Performance
Caster Available

Easier, more responsive starts
and rolling than mold on rubber

Resists and rejects metal
shavings, chips and other debris

Impact resistant with
maximum shock absorption



Caster Kit 650
6"x 2", Poly Core,
Round TPR Tread
(provides 1,500 lb cap.)
add **-650** to model #



Caster Kit 850
8"x 2", Poly Core
Round TPR Tread
(provides 2,000 lb cap.)
add **-850** to model #



Caster Kit 820
8" Cast Iron Core
Mold on Rubber
Square Tread
(provides 2,500 lb cap.)
add **-820** to model #

Welded Deck Design Available with
Full Perimeter Bumper

For Black add **-300** to model #

For non-marking Gray add **-310** to model #

And


Carpeted Deck, add **-C** to model #

*bumper required with carpeted deck

Optional Floor Locks

For use with 6" casters add **-060** to model #

For use with 8" casters add **-080** to model #



NEW DESIGN

Lighter Weight!
Improved Traction!
Built in Handles!

- Save Time and Money
- Reduce Risks of Injury and Fatigue
- Speeds Loading/Unloading
- Transports easily in your delivery vehicle
- Ideal for city deliveries where space is limited
- Widths and lengths to suit any application
- **Two Year Warranty!**


SPECIFICATIONS										
Type	Height Range (In)		Length (Ft)	Cap. Lbs.	26" Width		28" Width		38" Width	
	Min	Max			Model #	Wt (Lbs)	Model #	Wt (Lbs)	Model #	Wt (Lbs)
A	6	21	6	2000	-	-	PR-2806-A	48	PR-3806-A	61
	6	25	7	1800	-	-	PR-2807-A	56	PR-3807-A	70
	6	29	8	1700	-	-	PR-2808-A	63	PR-3808-A	79
	6	33	9	1650	-	-	PR-2809-A	70	PR-3809-A	88
	6	38	10	1500	-	-	PR-2810-A	77	PR-3810-A	97
	6	46	12	1400	-	-	PR-2812-A	92	PR-3812-A	115
	6	54	14	1200	-	-	PR-2814-A	107	PR-3814-A	133
	6	62	16	1000	-	-	PR-2816-A	121	PR-3816-A	151
F	6	23	6	2000	PR-2606-F	47	PR-2806-F	49	PR-3806-F	62
	6	27	7	1800	PR-2607-F	54	PR-2807-F	57	PR-3807-F	71
	6	31	8	1700	PR-2608-F	61	PR-2808-F	64	PR-3808-F	80
	6	35	9	1650	PR-2609-F	68	PR-2809-F	71	PR-3809-F	89
	6	40	10	1500	PR-2610-F	75	PR-2810-F	79	PR-3810-F	98
	6	48	12	1400	PR-2612-F	89	PR-2812-F	93	PR-3812-F	116
	6	56	14	1200	PR-2614-F	103	PR-2814-F	108	PR-3814-F	134
	6	64	16	1000	PR-2616-F	117	PR-2816-F	122	PR-3816-F	152



To suit your needs better, two types of ramps are available:



Type A
 The level-off apron overlaps the truck bed
 Safety chain (18") standard




Type F
 Steel hooks lock onto the truck bed providing flush-type direct entry

OPTIONAL UNDER TRUCK CARRIERS


Available for Type F Hook End ONLY

C designates carrier, then width, length and open or closed.

Ramp Width	Ramp Length	Open Carrier P/N	Closed Carrier P/N
26"	14'	C2614O	C2614C
26"	16'	C2616O	C2614C



Other sizes available on a special order basis and will be non-returnable. Consult factory for pricing.



NEW PUNCHED DESIGN


- Holes are punched in the material, provides superior traction
- Won't collect ice, mud, snow, or debris
- Punched design reduces the weight without sacrificing strength
- Custom widths available
- Steel hooks lock onto truck bed for flush-type direct entry

SPECIFICATIONS									
Height Range (In) Min Max		Length (Ft)	Cap. (Lbs)	26" Width		28" Width		38" Width	
				Model #	Wt. (Lbs)	Model #	Wt. (Lbs)	Model #	Wt. (Lbs)
6	23	6	2000	PRP-2606-F	44	PRP-2806-F	45	PRP-3806-F	58
6	27	7	1800	PRP-2607-F	51	PRP-2807-F	53	PRP-3807-F	67
6	31	8	1700	PRP-2608-F	57	PRP-2808-F	60	PRP-3808-F	75
6	35	9	1650	PRP-2609-F	64	PRP-2809-F	67	PRP-3809-F	83
6	40	10	1500	PRP-2610-F	70	PRP-2810-F	74	PRP-3810-F	92
6	48	12	1400	PRP-2612-F	84	PRP-2812-F	88	PRP-3812-F	108
6	56	14	1200	PRP-2614-F	97	PRP-2814-F	101	PRP-3814-F	125
6	64	16	1000	PRP-2616-F	111	PRP-2816-F	115	PRP-3816-F	142

Speeds Loading/Unloading and Material Movement in Warehouse or at Production Lines




Model #4248-6T



Optional Handle



Model #2424-6T



Model #4848-6T

Light - Average weight only 40 lbs. Make possible return of number of dollies to leading point manually.

Rugged - Strong extruded aluminum frame and steel axles.

Maneuverable - Tilt Construction with 360 degree turning. Non-tilt also available.


Rollers - 3.5" rollers with sealed bearings.

All Popular Sizes - From 36"x36" to 48"x48".

Capacities - 4,000 to 8,000 pounds.

Economic Benefits - Frees fork lift trucks from short hauls. Greater worker safety and reduced labor time.


Size W x L Length is Travel Direction	4,000 Lb Capacity 6 Roller		6,000 Lb Capacity 8 Roller		8,000 Lb Capacity 10 Roller	
	Model #	Wt (Lbs)	Model #	Wt (Lbs)	Model #	Wt (Lbs)
36" x 36"	3636-6T	32	3636-8T	37	3636-10T	40
36" x 42"	3642-6T	34	3642-8T	40	3642-10T	43
36" x 48"	3648-6T	36	3648-8T	41	3648-10T	44
40" x 48"	4048-6T	36	4048-8T	42	4048-10T	45
42" x 42"	4242-6T	37	4242-8T	43	4242-10T	46
42" x 48"	4248-6T	37	4248-8T	43	4248-10T	46
48" x 48"	4848-6T	38	4848-8T	44	4848-10T	47
24" x 24"	2424-6T	34				



Deck option available - consult factory

Non Tilt Type

If a non-tilt type of Pallet Dolly is desired, delete the "T" and add "NT" to the model number when ordering - No extra charge for the non-tilt type dollies



Two handle loops and one handle are available as optional equipment - push or pull either end
Add -H to model #
Example: 4848-6T-H

To order center support crossbar as an option
Add -CB to model #
Example: 3636-6T-CB



To Select Your Ramp:

Ramp selection is based on the following three items:


A Width - Based on the maximum wheel width of your largest vehicle.
For double wheel vehicles, choose the 24" width and use the ramp at the inside wheel location.

B Height - Determined by the following formula:
Dock Height + 2" = _____
minus Truck Bed Height = _____
Choose the next highest standard height in chart.

C Length - The longer the ramp, the less incline angle. Choose a length with an incline angle that your loaded vehicles can negotiate easily.



CAPACITY FOR ALL MODELS = 12,000 LBS PER RAMP							
Height (In)	Length (In)			18" Wide		24" Wide	
	Overall	Level	Incline	Model #	Wt (Lbs)	Model #	Wt (Lbs)
	6	48	30	18	PR-18-6-48	64	PR-24-6-48
60		42	18	PR-18-6-60	77	PR-24-6-60	94
102		84	18	PR-18-6-102	126	PR-24-6-102	145
8	54	30	24	PR-18-8-54	78	PR-24-8-54	94
	60	36	24	PR-18-8-60	85	PR-24-8-60	103
	108	84	24	PR-18-8-108	147	PR-24-8-108	169
10	60	30	30	PR-18-10-60	95	PR-24-10-60	115
	66	36	30	PR-18-10-66	102	PR-24-10-66	124
	72	42	30	PR-18-10-72	111	PR-24-10-72	133
	114	84	30	PR-18-10-114	166	PR-24-10-114	188
12	72	36	36	PR-18-12-72	125	PR-24-12-72	143
	78	42	36	PR-18-12-78	137	PR-24-12-78	153
	120	84	36	PR-18-12-120	188	PR-24-12-120	213




Wheel Chocks

RUBBER

MODEL #RWC-1

Rubber Construction
Ribbed Tire Face
Extra Strong, Lightweight
9 lbs. each
9.5"W x 8"H x 6"D



ALUMINUM

MODEL #AWC-888


Extruded Aluminum
Ribbed Tire Face
Extra Strong, Lightweight
7 lbs. each
8"W x 7.5"H x 7.5"D

ATTENTION!!

Wheels
MUST BE
Chocked!
AN
OSHA
REQUIREMENT

Optional
**ANTI-
PILFERAGE**
Kit

MODEL APK-10



Kit includes: One 10 foot steel chain and attaching bracket

We were one of the first companies in the industry to utilize light metal robotic welding.

This advanced technology provides high volume welding with an accuracy and consistency that was not attainable before.



Streamlined processes and work flows allows large orders to be processed quickly. Average turnaround time for a stocking order is 5-7 business days - regardless of size. Think about that the next time you receive a large order that needs to be filled - FAST!




Our “hands on” approach to product development allows us to continue providing the products that meet today's challenges as well as tomorrow's. Working with the users of our products keeps us in tune with the ever changing delivery environment.



Local distributors play a key role in maintaining communication between you and manufacturing. This keeps us up to date on current trends and lets us see “into the future” as delivery methods evolve.



On site training and demonstration facilities let everyone from manufacturing, engineering, customer service and sales experience first hand how the products work. This helps us maintain our high level of service. End users also visit our facilities and lend key information in developing new products for the real world.





Your Local Distributor:

Ask about our no-obligation 30 day demo program!

Our Complete Catalog is Available Online at

www.bpmfg.com

1-800-334-7141 bpsales@bpmfg.com

b&p ***Manufacturing***
ENGINEERED DELIVERY PRODUCTS

8051 East Boon Road Cadillac, Michigan 49601 Tel: 231-775-2229 Fax: 231-775-0013